

Condensate drains

ABAC offers a complete range of condensate drains, used in the compressed air industry to discharge the condensate from the tanks, filters, dryers and separators: automatic drains with float sensor, electronic automatic drains, timed drains.



G120 -Mechanical condensate drain

The G120 mechanical condensate drain requires no electrical connection and is recommended for areas subject to explosion or fire hazards



E200 -Timed condensate drain

The timed condensate drain works by means of a servo-controlled valve That opens periodically based on the time set



LD -Smart condensate drain

The LD capacitive drain range uses an electronic sensor that detects the level of condensate inside the drain body and controls the opening of the drain valve

Model	Part number	Working pressure range bars	Compressor capacity	Dryer capacity m³/h	Filter capacity m³/h	Connection Ø	Power supply	Protection rating IP
Mechanical G120	0079500000	0-16	5,000	10,000	50,000	1/2"	-	IP65
Timer E200	0079520000	0-16	5,000	10,000	50,000	3/8"	230/50	IP65
Electronic LD200	4101000212	0.2-16	900	1,800	9,000	1/2"	230/50	IP65
Electronic LD202	4101000213	0.2-16	1,800	3,600	18,000	1/2"	230/50	IP65
Electronic LD203	4101000214	0.2-16	9,500	19,000	95,000	1/2"	230/50	IP65

